

<b>Soort</b>	<b>Volume (l)</b>	<b>Afmetingen L x ø (mm)*</b>	<b>Gewicht (kg)</b>	<b>Max. druk (bar)</b>
<b>Slim 15</b>	15	520 x 295	10.5	7.0
<b>Slim 20</b>	20	645 x 295	11.5	7.0
<b>Slim 25</b>	25	765 x 295	13.5	7.0
<b>Basic 24</b>	24	470 x 395	14.0	7.0
<b>Basic 30</b>	30	535 x 395	17.0	7.0
<b>Basic 40</b>	40	640 x 395	20.0	7.0
<b>Basic 50</b>	50	760 x 395	23.0	7.0
<b>Basic 75</b>	75	1050 x 395	29.0	7.0
<b>Slim 25 anti-flare</b>	25	765 x 295	13.5	7.0
<b>Basic 24 anti-flare</b>	24	470 x 395	14.0	7.0
<b>Square 16</b>	16	400 x 180 x 560 ((L x B x H))	16.0	5.5
<b>Basic 24 double coil</b>	24	470 x 395	14.0	7.0
<b>Basic 40 double coil</b>	40	640 x 395	20.0	7.0
<b>Basic 75 double coil</b>	75	1050 x 395	29.0	7.0

\* Inclusief thermostaat mengkraan